



# Sport System

## multisport ultra 20

<b>Colour : Green</b>				
<b>Description : Sanded version artificial turf , Heat-proof、Frost-proof, UV-resistance , Environmental protection</b>				
<b>。 Uses : Multisport</b>				
<b>Specification</b>				
<b>Yarn:</b>	ECF8800H2V			
Type :	100% UV Stabilized Polyethylene[PE]			
	8800Dtex			
Width :	12.5mm(±5%)			
Thickness :	70micron(±5%)			
	<b>Installation Instruction</b>			
	Base Quality : The base must be meet the follow min requirements			
	Level : <10 mm when under 3m (Ref.EN22768testing standard) Tolerance: 1mm			
Tuft Gauge :	3/8"			
Tuft Frame :	Straight			
Pile Height:	20mm(±10%)			
Pile Weight :	905.52g/Sqm(±10%)			
Stitch Rate :	200Stiches/m			
	Installation : Turf roll jointed by the connection strap and Polyurethane glue supplied by Taishan			
Stitch Density:	21000 Stiches/Sqm (±5%)			
	Filling of silicon sand and rubber under dry weather			
<b>Backing</b>				
The first layer :	Composite PP			
	Maintain : Suggestion full-scale cleaning on fixed date and scrubbing every week.			
Weight :	238g/Sqm			
	Accessories : White mark line			
Coating Weight:	900g/Sqm			
	(Width: each roll 50,75,100,120 mm or confirm with the order)			
Type :	BASF SBR Latex			
	Quality guarantee : Ref.DIN18035standard guarantee more than 8 years under normal use on the large-scale fields			
	Extended guarantee available.			
Total Weight :	2043.52g/Sqm(±10%)			
	<b>Testing</b>			
		Test	Method	Result
Water drainage:	≥64 liter/m <sup>2</sup> ·minute	Wear resistant : shock absorption	EN13672	55-70%
<b>Packing</b>		resistance	EN13672	25-50.N m
Roll length :	Confirmation with order	Weather resistant : anti corruption	EN 13864	
Roll width :	as required	Depigmentation	EN13864	
		Pile retention :	≥40N	46.8N